



Terrasoft®

Power glue for joints

Hybrid adhesive for joint bonding

Free of solvent, isocyanate and silicone. almost odourless. Very good, mostly primerless adhesion on almost all, even damp, substrates. After curing permanently elastic. Fresh and seawater resistant.

SCOPE OF APPLICATION

All waterproofing and permanent bonding: on smooth and porous surfaces, inside and outside, even in damp rooms and on damp surfaces. Hybrid adhesive and sealant is used for bonding and sealing all common building materials

usage tips

The surfaces must be clean, dust and grease-free. Press out the cartridge with a hand or compressed air pistol.

As a seal: apply evenly. The smoothing, if necessary, must be done with a soap solution before a skin has had time to form. Clean tools with turpentine (crystal oil) immediately after use. Further information on product safety and handling can be found in our safety data sheet.

Structural bonding, stress-free between metals, plastics (except PE, PP and PTFE) and hardwoods

Compensates for unevenness and material tensions

Very good paint-compatibility according to DIN 52452, can be over-painted wet-on-wet.



Colourfast, weather and UV resistant

Suitable for sanitary applications

non-corrosive

Bubble-free curing even at high temperatures

No staining on porous substrates such as e.g. natural stone, ashlar, marble, granite, etc..



Terrasoft Power for glue joints
black