



Terrasoft®

Selective glueing

Adhesive PUR 1K for selective & strip gluing from rubber moulded article

Curing one-component adhesive by humidity and sealant based on polyurethane. Visco plastic. Functioning after approx. 3 hours, final strength after approx. 24 hours. To ensure durability, note the information on the cartridges. Store in a cold and dry place (+5 °C to +25 °C).

WORK PREPARATION

Surfaces must be clean, dry and grease-free. Adhesion and compatibility with plastics and paints must be object-related checked. Processing like silicone - Do not open the lid, just press it

GLUING

Apply material to the substrate with spatula or putty gun. The application thickness depends on the nature of the materials to be bonded. Lay on the counter material within 10 minutes and press on. Due to the pasty consistency of the material, it is advisable to fix the composite. The curing depends on the layer thickness and the humidity.

REQUIREMENT

For approx. 3 m² 1 cartridge à 370 g is needed.

Observe the instructions of the manufacturer
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Avoid inhalation of mist / vapor / aerosol.
Wear protective gloves.
Contains diphenyl methane-4,4'-diisocyanate
Contains isocyanates



Terrasoft Selective glueing
red



Terrasoft Selective glueing
black